

# RT125 TRACTOR ATTACHMENTS



**BH120 BACKHOE**

DIMENSIONS	U.S.	METRIC
Transport height	118 in	2997 mm
Ground clearance	29 in	736 mm
Digging depth, max	112 in	2844 mm
Reach from swing pivot	158 in	4013 mm
Bucket width	12-24 in	300-610 mm
Backhoe weight without bucket	3,300 lb	1497 kg
Swing arc	180°	



**CT120H TRENCHING ATTACHMENT**

DIMENSIONS	U.S.	METRIC
Angle of departure	23.7°	
Trench depth, max	97 in	2463 mm
Trench width, max	24 in	610 mm
Transport height	124 in	3251 mm
Transport length	115 in	2921 mm
Attachment weight	1,750 lb	794 kg



**PT120H COMBO ATTACHMENT**

TRENCHER DIMENSIONS	U.S.	METRIC
Trench depth, max	70 in	1780 mm
Trench width	6-12 in	150-300 mm
Transport length*	126 in	3200 mm
Transport height*	126 in	3200 mm
Angle of departure	22°	

\*Dimensions w/48" boom

PLOW DIMENSIONS	U.S.	METRIC
Angle of departure, transport, no blade	30°	
Angle of departure, transport, 24-inch blade	27°	
Angle of departure, transport, 30-inch blade	22°	
Attachment length, fully lowered, no blades	103 in	2616 mm
Attachment length, fully raised, no blades	70 in	1778 mm
Cover depth*	36 in	914 mm
Attachment weight without boom, chain, or plow blade	3,065 lb	1390 kg

\*Suggested maximum. Plow blade used will be determined by job requirements and soil conditions.



# RT125 TRACTOR ATTACHMENTS



**VP120H PLOWING ATTACHMENT**

DIMENSIONS	U.S.	METRIC
Angle of departure, transport, no blade	47.5°	
Angle of departure, transport, 24-inch blade	30°	
Angle of departure, transport, 30-inch blade	24°	
Attachment length, fully lowered, no blade	97 in	2464 mm
Attachment length, fully raised, no blade	78 in	1981 mm
Cover depth*	42 in	1067 mm
Attachment weight, without plow blade	2,600 lb	1180 kg

\*Suggested maximum. Plow blade used will be determined by job requirements and soil conditions.



**ST120H TRENCHING ATTACHMENT**

DIMENSIONS	U.S.	METRIC
Angle of departure	24°	
Trench depth, max	94 in	2387.6 mm
Trench width, max	24 in	610 mm
Transport length	126 in	3200 mm
Attachment weight	2,350 lb	1066 kg



**RS40 SAWING ATTACHMENT**

DIMENSIONS	U.S.	METRIC
Trench depth	40 in	1016 mm
Trench width	4.5, 6, 8 in	115, 150, 203 mm
Transport height - attachment	130 in	3302 mm
Angle of departure	19°	
Attachment weight	5,900 lb	2676 kg



**RC30 REEL CARRIER**

DIMENSIONS	U.S.	METRIC
Reel diameter, max	96 in	2438 mm
Internal width	54 in	1372 mm
Capacity	2,500 lb	1134 kg